

## II. CLAIM AMENDMENTS

1. (Currently Amended) A process for producing a continuous, intermediate belt for receiving heat-fusible toner images from a photoreceptor surface and for simultaneously fusing and completely transferring said image to a copy sheet as glossy-surface images, said process comprising the steps of:

(a) providing a continuous support fibrous fabric material having on at least the outer surface thereof a thin layer of elastomeric composition which impregnates, penetrates and anchors to said fibrous fabric material;

(b) applying a thin primer layer of a moisture-curable polyfunctional silicone composition to said thin layer of elastomeric composition and hydrolyzing said silicone composition to form a chemical bond between said elastomeric layer and the hydrolyzed silicone composition,

(c) applying over said hydrolyzed silicone primer layer a thin outer layer of a heat-curable elastomer polymer which is reactive with the hydrolyzed silicone primer layer to form a chemical bond therewith; and

(d) heat-curing said elastomer polymer at elevated temperatures to form a dry, outer surface layer which is chemically-bonded to said primer layer as a smooth release surface for said heat fusible toner images.

2. (Original) A process according to claim 1 in which said support of fibrous fabric comprises a woven fabric having high heat-resistance and mechanical strength.

3. (Original) A process according to claim 1 in which said elastomeric composition impregnated into said support comprises a synthetic rubber.

4. (Previously Amended) A process according to claim 1 in which said primer layer comprises 3-aminopropyl triethoxysilane.

5. (Original) A process according to claim 1 in which said elastomer polymer comprises a vinylidene fluoride polymer.

6. (Original) A process according to claim 5 in which said elastomer polymer is a tetrapolymer of vinylidene fluoride, hexafluoropropylene, tetrafluoroethylene and a cure site monomer.